## § 60.442

Coating applicator means an apparatus used to apply a surface coating to a continuous web.

Coating line means any number or combination of adhesive, release, or precoat coating applicators, flashoff areas, and ovens which coat a continuous web, located between a web unwind station and a web rewind station, to produce pressure sensitive tape and label materials.

Coating solids applied means the solids content of the coated adhesive, release, or precoat as measured by Reference Method 24.

Flashoff area means the portion of a coating line after the coating applicator and usually before the oven entrance.

Fugitive volatile organic compounds means any volatile organic compounds which are emitted from the coating applicator and flashoff areas and are not emitted in the oven.

*Hood or enclosure* means any device used to capture fugitive volatile organic compounds.

*Oven* means a chamber which uses heat or irradiation to bake, cure, polymerize, or dry a surface coating.

Precoat means a coating operation in which a coating other than an adhesive or release is applied to a surface during the production of a pressure sensitive tape or label product.

Solvent applied in the coating means all organic solvent contained in the adhesive, release, and precoat formulations that is metered into the coating applicator from the formulation area.

Total enclosure means a structure or building around the coating applicator and flashoff area or the entire coating line for the purpose of confining and totally capturing fugitive VOC emissions.

VOC means volatile organic compound.

- (b) All symbols used in this subpart not defined below are given meaning in the Act or in subpart A of this part.
- a=the gas stream vents exiting the emission control device.
- b=the gas stream vents entering the emission control device.
- $C_{aj}$ =the concentration of VOC (carbon equivalent) in each gas stream (j) exiting the emission control device, in parts per million by volume.

- $C_{\rm bi}$ =the concentration of VOC (carbon equivalent) in each gas stream (i) entering the emission control device, in parts per million by volume.
- $C_{fk}$ =the concentration of VOC (carbon equivalent) in each gas stream (k) emitted directly to the atmosphere, in parts per million by volume.
- G=the calculated weighted average mass (kg) of VOC per mass (kg) of coating solids applied each calendar month.
- $M_{\rm ci}$ =the total mass (kg) of each coating (i) applied during the calendar month as determined from facility records.
- $M_{\rm r}$ =the total mass (kg) of solvent recovered for a calendar month.
- Q<sub>aj</sub>=the volumetric flow rate of each effluent gas stream (j) exiting the emission control device, in dry standard cubic meters per hour.
- $Q_{\rm bi}$ =the volumetric flow rate of each effluent gas stream (i) entering the emission control device, in dry standard cubic meters per hour.
- $Q_{fk}$ =the volumetric flow rate of each effluent gas stream (k) emitted to the atmosphere, in dry standard cubic meters per hour.
- R=the overall VOC emission reduction achieved for a calendar month (in percent).
- $R_q$ =the required overall VOC emission reduction (in percent).
- W<sub>oi</sub>=the weight fraction of organics applied of each coating (i) applied during a calendar month as determined from Reference Method 24 or coating manufacturer's formulation data.
- W<sub>si</sub>=the weight fraction of solids applied of each coating (i) applied during a calendar month as determined from Reference Method 24 or coating manufacturer's formulation data.

## §60.442 Standard for volatile organic compounds.

- (a) On and after the date on which the performance test required by §60.8 has been completed each owner or operator subject to this subpart shall:
- (1) Cause the discharge into the atmosphere from an affected facility not more than 0.20 kg VOC/kg of coating solids applied as calculated on a weighted average basis for one calendar month; or
- (2) Demonstrate for each affected facility;
- (i) A 90 percent overall VOC emission reduction as calculated over a calendar month; or
- (ii) The percent overall VOC emission reduction specified in \$60.443(b) as calculated over a calendar month.